















SAT Coaxial Cable (90 dB)

for high requirements with satellite and cable compatible F connectors. SCHWAIGER® TV systems. Due to its higher screening offers a suitable stripping tool. efficiency of 90 dB, it offers additional protection against electromagnetic interference. The cable can be shortened as

This SCHWAIGER® coaxial cable is suitable desired and then be equipped with



ARTICLE INFORMATION

Article Nr EAN

KOX740 052 4004005740035



Last updated: 23.03.2016



productinformation



FEATURES (KOX740 052)

- shielded 3 times for additional protection against electromagnetic signal interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency

TECHNICAL DATA

quality	** Professional
Norm/Classifacation	class A
Impedance	75 Ohm
Cable design	1.02 mm (inner conductor) 4.5 mm (dielectric) 7 mm (sheath)
Shielding value	up to 1000 MHz > 95 dB up to 2150 MHz > 90 dB
Shielding	shielded 3 times
Shielding material	aluminium composite film/80-wire aluminium braid/aluminium composite film

Attenuation on 100 m	4,3 dB up to 50 MHz 6,1 dB up to 100 MHz 13 dB up to 470 MHz 18,5 dB up to 860 MHz 21 dB up to 950 MHz 27 dB up to 1750 MHz 31 dB up to 2150 MHz
Inner conductor	CCS
Cable length	40 m
Material of product	plastic
Colour	white
packaging	shrink foil

Last updated: 23.03.2016